

ROW CROP RADIAL TYRES

90 & 95 SERIES

- Round shoulders minimize influence on the crop roots.
- Optimum lug shape & angle provide an excellent grip.
- Long service life thanks to the use of a wear resistant tread compound.



	SIZE	PATTERN	RIM WIDTH (inch)	TUBE TYPE/ TUBELESS	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY				INFLATION PRESSURE	
					(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(inch)	(mm)	(32nds)	40KPH / 25MPH MAX LOAD	(kg)	(lbs)	50KPH / 30MPH MAX LOAD	(kg)	(lbs)
32"	210/95R-32 (REPLACES 8.3R-32) 120 A8 /B	RC-999	W7	TUBELESS	213	8.4	1212	47.7	559	20.0	3658	144.0	31	39	1180	2596	1180	2596	46	58
	230/95R-32 (REPLACES 9.5R-32) 128 A8 /B	RC-999	W8	TUBELESS	239	9.41	1252	49.3	584	23.0	3759	148.0	33	41	1804	3970	1804	3970	46	58
36"	270/95R-32 (REPLACES 11.2R-32) 136 A8 /B	RC-999	W8	TUBELESS	264	10.4	1325	52.2	609	24.0	5013	158.0	34	43	2245	4940	2245	4940	46	58
	230/95R-36 (REPLACES 9.5R-36) 130 A8 /B	RC-999	W8	TUBELESS	238	9.4	1351	53.2	609	24.0	4064	160.0	33	41	1904	4190	1904	4190	46	58
	270/95R-36 (REPLACES 11.2R-36) 139 A8 /B				UNDER DEVELOPMENT															
38"	270/95R-38 (REPLACES 11.2R-38) 140 A8 /B				UNDER DEVELOPMENT															
44"	230/95R-44 (REPLACES 9.5R-44) 134 A8 /B	RC-999	W8	TUBELESS	239	9.4	1557	61.3	737	29.0	4699	185.0	33	41	2125	4675	2125	4675	46	58
	270/95R-44 (REPLACES 11.2R-44) 142 A8 /B	RC-999	W8	TUBELESS	264	10.4	1633	64.3	762	30.0	4902	193.0	34	43	2655	5840	2655	5840	46	58
46"	300/95R-46 (REPLACES 12.4R-46) 148 A8 /B				UNDER DEVELOPMENT															
	380/90R-46 (REPLACES 14.9R-46) 148 A8 /B				UNDER DEVELOPMENT															
48"	230/95R-48 (REPLACES 11.2R-48) 136 A8 /B	RC-999	W8	TUBELESS	239	9.4	1656	65.2	1656	31.0	4978	196.0	33	41	2245	4940	2245	4940	46	58
	270/95R-48 (REPLACES 11.2R-48) 144 A8 /B	RC-999	W8	TUBELESS	264	10.4	1732	68.2	812	32.0	5257	207.0	34	43	2806	6175	2806	6175	46	58